STATE OF ILLINOIS
DEPARTMENT OF
REGISTRATION AND
EDUCATION
WILLIAM H. ROBUSON.
DIRECTON, SPRINGFIELD
BOARD OF NATURAL
RESOURCES AND
CONSERVATION

CHAIRMAN - WILLIAM H. RCBINSON SEGLOGY - LAURENCE L. SLORS CHEMISTRY - - NOGER ADAMS ENGINEERING - POBERT H. ANDERSON E.OLOGY - - THOMAS PARK FORESTRY - - CHARLER E OLMSTED UNIVERSITY OF ILLINOIS

DEAN WILLIAM L EVERITY

SOUTHERN ILLINOIS UNIVERSITY

PRESIDENT BELYTE W MORRIS

ILLINOIS STATE GEOLOGICAL SURVEY

NATURAL RESOURCES BUILDING PEABODY EAST OF SOUTH SIXTH URBANA, ILLINOIS 61801 TELEPHONE 217 344-1481

JOHN C. FRYE. CHIEF

P. O. Rox I Warrenville, Illinois 60555 March 18, 1971

Cook County - Solid Waste Disposal Palos Hills/De Boer

RECEIVED

MAR 22 1971

ENVIRONMENT OF MEMORS ASSETTLY

Mr. C. E. Clark, Chief Bureau of Land Pollution Control Environmental Protection Agency 2400 West Jefferson Springfield, Illinois 62706

Dear Mr. Clark:

This is in response to your letter of March 8, 1971, requesting a description of the hydrogeology in the vicinity of a solid waste disposal site located in the NE4 of Section 13, T. 37 N., R. 12 E., Cook County.

The site was visited on March 16, 1971. It is located immediately north of Stony Creek, and, according to Hydrologic Investigations Atlas HA-145 of the Palos Park Quadrangle, the area was flooded in 1954. The site is currently operating, and appears to be receiving mainly industrial wastes, such as wooden pallets and paper.

At the time of the visit a trench was being excavated in the southern part of the site immediately north of Stony Creek. The materials exposed consisted of a coarse, poorly sorted gravel. There were also piles of materials scattered over the site which apparently had been excavated from the refuse trenches. These piles contained sand and gravel, silty clay till, and what appeared to be ashes and cinders, suggesting that the area may have originally been an open burning dump. Water was present in the base of the trench which was being excavated, however, this was probably surface runoff.

Our surface and subsurface mapping are not in agreement as to the types of glacial drift materials present at this site. Well records indicate that the glacial drift is approximately 40 feet thick and contains a basal sand and gravel aquifer 15 to 25 feet thick. Surficial mapping shows thin valley train sands and gravels immediately overlying



Mr. Clark - 2

the bedrock. Site borings would be necessary to resolve this difference. The Silurian Dolomite aquifer underlies the glacial ddift.

The State Geological Survey has records of three wells completed in the Silurian Dolomite aquifer within one-half mile of this site. These records are not complete, and other wells may be present in the area, or the recorded wells may have since been abandoned.

The top of the zone of saturation is probably within 10 feet of the ground surface at the elevation of the water in Stony Creek. Under natural conditions ground-water movement from the site is probably into Stony Creek or downward into the Silurian Dolomite aquifer. If dissolved solids are produced at this site they would have access to Stony Creek, and possibly to the underlying Silurian Dolomite, as well.

If further information is desired on this site, we would suggest that borings be made to define the drift materials above the Silurian aquifer, and the direction of ground-water movement.

Yours truly,

George M. Hughes

Heorge Hughes

Associate Geologist Northeastern Illinois Office Section of Ground-Water Geology and Geophysical Exploration

GMH/jge

cc: Benn Leland